

HEIDI-O

~50° x 11° oval beam

SPECIFICATION:

Dimensions	Ø 21.6 mm
Height	11.9 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
HEIDI-O	Single lens	PMMA	clear	
HEIDI-TAPE	Tape	Acrylic foam	black	



ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CA11266_HEIDI-O	Single lens	3264	204	204	9.7
» Box size: 480 x 280 x 300 mm					




See also our general installation guide: www.ledil.com/installation_guide


OPTICAL RESULTS (MEASURED):




LED XB-D
 FWHM / FWTM 54.0 + 10.0° / 77.0 + 27.0°
 Efficiency 87 %
 Peak intensity 3.9 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:




LED XB-H
 FWHM / FWTM 53.0 + 11.0° / 78.0 + 34.0°
 Efficiency 83 %
 Peak intensity 3.3 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:



LED XD16
 FWHM / FWTM 52.0 + 10.0° / 75.0 + 30.0°
 Efficiency 89 %
 Peak intensity 3.2 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:




LED XP-E
 FWHM / FWTM 48.0 + 10.0° / 70.0 + 30.0°
 Efficiency 87 %
 Peak intensity 4.1 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:




OPTICAL RESULTS (MEASURED):





LED XP-E2
 FWHM / FWTM 54.0 + 9.0° / 75.0 + 23.0°
 Efficiency 85 %
 Peak intensity 4.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED XP-G
 FWHM / FWTM 47.0 + 14.0° / 72.0 + 36.0°
 Efficiency 87 %
 Peak intensity 3.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED XP-G2
 FWHM / FWTM 52.0 + 11.0° / 76.0 + 32.0°
 Efficiency 91 %
 Peak intensity 3.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XP-G3
 FWHM / FWTM 51.0 + 13.0° / 77.0 + 37.0°
 Efficiency 91 %
 Peak intensity 3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





OPTICAL RESULTS (MEASURED):




LED XQ-E HD
 FWHM / FWTM 55.0 + 8.0° / 75.0 + 22.0°
 Efficiency 93 %
 Peak intensity 4.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED XQ-E HI
 FWHM / FWTM 53.0 + 7.0° / 73.0 + 21.0°
 Efficiency 90 %
 Peak intensity 4.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED XT-E
 FWHM / FWTM 52.0 + 12.0° / 78.0 + 35.0°
 Efficiency 91 %
 Peak intensity 3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED LUXEON C
 FWHM / FWTM 53.0 + 9.0° / 75.0 + 25.0°
 Efficiency 81 %
 Peak intensity 4.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):


LUMILEDS

LED LUXEON CZ
 FWHM / FWTM 53.0 + 7.0° / 72.0 + 20.0°
 Efficiency 92 %
 Peak intensity 5.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LUMILEDS

LED LUXEON T
 FWHM / FWTM 52.0 + 12.0° / 76.0 + 33.0°
 Efficiency 81 %
 Peak intensity 3.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LUMILEDS

LED LUXEON TX
 FWHM / FWTM 54.0 + 12.0° / 77.0 + 31.0°
 Efficiency 82 %
 Peak intensity 3.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LUMILEDS


LED LUXEON Z
 FWHM / FWTM 55.0 + 7.5° / 73.0 + 20.0°
 Efficiency 87 %
 Peak intensity 4.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):


LUMILEDS

LED LUXEON Z ES
 FWHM / FWTM 54.0 + 9.6° / 74.0 + 25.0°
 Efficiency 85 %
 Peak intensity 3.8 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:




NICHIA

LED NCSxx19A
 FWHM / FWTM 46.0 + 12.0° / 70.0 + 34.0°
 Efficiency 82 %
 Peak intensity 3.3 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:




NICHIA

LED NCSxx19B
 FWHM / FWTM 55.0 + 11.0° / 77.0 + 29.0°
 Efficiency 83 %
 Peak intensity 3.6 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:











NICHIA

LED NVSxx19A
 FWHM / FWTM 50.0 + 12.0° / 76.0 + 35.0°
 Efficiency 82 %
 Peak intensity 3 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):


<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C FWHM / FWTM 48.0 + 15.0° / 74.0 + 36.0° Efficiency 82 % Peak intensity 2.7 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C FWHM / FWTM 54.0 + 12.0° / 78.0 + 33.0° Efficiency 92 % Peak intensity 3.2 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOM Square CSSRM2/CSSRM3 FWHM / FWTM 52.0 + 13.0° / 80.0 + 32.0° Efficiency 80 % Peak intensity 3.7 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOM Square EC FWHM / FWTM 48.0 + 12.0° / 74.0 + 30.0° Efficiency 86 % Peak intensity 3.5 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		

OPTICAL RESULTS (MEASURED):

OSRAM

Opto Semiconductors


LED OSLON SSL 150
 FWHM / FWTM 50.0 + 8.0° / 75.0 + 22.0°
 Efficiency 85 %
 Peak intensity 4.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OSRAM


Opto Semiconductors

LED OSLON SSL 80
 FWHM / FWTM 47.0 + 8.0° / 73.0 + 27.0°
 Efficiency 83 %
 Peak intensity 4.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





SAMSUNG

LED LH181A
 FWHM / FWTM 52.0 + 12.0° / 76.0 + 36.0°
 Efficiency 93 %
 Peak intensity 2.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG



LED LH181B
 FWHM / FWTM 53.0 + 13.0° / 75.0 + 35.0°
 Efficiency 90 %
 Peak intensity 2.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):



SAMSUNG

LED LH351B
 FWHM / FWTM 51.0 + 13.0° / 77.0 + 34.0°
 Efficiency 84 %
 Peak intensity 3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LH351Z
 FWHM / FWTM 54.0 + 12.0° / 78.0 + 32.0°
 Efficiency 83 %
 Peak intensity 3.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SEOUL SEMICONDUCTOR

LED Z5
 FWHM / FWTM 50.0 + 9.0° / 74.0 + 23.0°
 Efficiency 86 %
 Peak intensity 4.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SEOUL SEMICONDUCTOR


LED Z5M1/Z5M2
 FWHM / FWTM 53.0 + 11.0° / 77.0 + 32.0°
 Efficiency 85 %
 Peak intensity 3.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):

SHARP


LED Double Dome (GM2BB)
FWHM / FWTM 50.0 + 16.0° / 79.0 + 40.0°
Efficiency 85 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):




LED XHP35.2 HI
 FWHM / FWTM 53.0 + 14.0° / 80.0 + 40.0°
 Efficiency 89 %
 Peak intensity 2.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XP-G4
 FWHM / FWTM 52.0 + 10.0° / 76.0 + 28.0°
 Efficiency 90 %
 Peak intensity 3.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED LUXEON 3030 HV
 FWHM / FWTM 55.0 + 11.0° / 78.0 + 28.0°
 Efficiency 90 %
 Peak intensity 3.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED LUXEON HL2Z
 FWHM / FWTM 54.0 + 12.0° / 76.0 + 29.0°
 Efficiency 90 %
 Peak intensity 3.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (SIMULATED):


LUMILEDS

LED LUXEON Rubix
 FWHM / FWTM 50.0 + 8.0° / 73.0 + 16.0°
 Efficiency 91 %
 Peak intensity 5.5 cd/lm
 LEDs/each optic 1
 Light colour Red
 Required components:




LUMILEDS

LED LUXEON SunPlus 20 Line (150 deg)
 FWHM / FWTM 52.0 + 10.0° / 76.0 + 20.0°
 Efficiency 87 %
 Peak intensity 4.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




NICHIA

LED NF2x757G
 FWHM / FWTM 54.0 + 12.0° / 78.0 + 29.0°
 Efficiency 91 %
 Peak intensity 3.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:







NICHIA




LED NFSx757G
 FWHM / FWTM 54.0 + 10.0° / 78.0 + 28.0°
 Efficiency 0 %
 Peak intensity 3.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (SIMULATED):

<p>NICHIA</p> <p>LED NVSxE21A FWHM / FWTM 54.0 + 11.0° / 76.0 + 28.0° Efficiency 88 % Peak intensity 3.3 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSCONIQ P 3030 FWHM / FWTM 53.0 + 8.0° / 75.0 + 20.0° Efficiency 89 % Peak intensity 4.5 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOM Black Flat (LUW HWQP) FWHM / FWTM 49.7 + 7.8° / 71.9 + 18.6° Efficiency 93 % Peak intensity 5 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOM SSL 150 FWHM / FWTM 51.0 + 8.0° / 74.0 + 18.0° Efficiency 91 % Peak intensity 4.9 cd/lm LEDs/each optic 1 Light colour Red Required components:</p>	

OPTICAL RESULTS (SIMULATED):

<p>OSRAM Opto Semiconductors</p> <p>LED SFH 4716S FWHM / FWTM 52.0 + 9.0° / 74.0 + 19.0° Efficiency 93 % LEDs/each optic 1 Light colour IR Required components:</p>	
<p>SEOUL SEMICONDUCTOR</p> <p>LED Z5M3 FWHM / FWTM 52.0 + 13.0° / 78.0 + 34.0° Efficiency 90 % Peak intensity 3 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>SEOUL SEMICONDUCTOR</p> <p>LED Z5M4 FWHM / FWTM 54.0 + 14.0° / 78.0 + 34.0° Efficiency 89 % Peak intensity 2.9 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)